


Target Development at SINQ

presented by

Werner Wagner

**Spallation Neutron Source Division
Paul Scherrer Institute, Switzerland**



Proton accelerator

**Neutron Spallation Source
SINQ**

Aare


Proton accelerator Facility at PSI

Proton synchrotron


- 590 MeV
- 1.8 mA
(routinely)

Serving

- Particle physics
- Muon spectroscopy
- Medicine
- Solid State Physics
and Materials Science



SINQ Targetstation



Vertical Section of the SINQ Facility

SINQ Targetstation

Meson experimental hall

Beam stop shielding

Proton beam

Target top shielding (concrete)

Water service area

Crane of neutron target hall
Cold moderator auxiliary equipment

Target bulk shielding

SINQ - Target

Neutron guides

Service and maintenance room


Target catcher



Target bulk shielding

tion of the SINQ Facility

Yearly accumulated proton charge on SINQ target (mAh)



What more
can we do?

upgrade potentials:

➤ Proton Accelerator beam power:

gain factor

- | | | |
|--------------|----------------------------------|----------|
| • today | 590 MeV x 1800 μ A = 1.06 MW | 1 (ref.) |
| • ~2008 | 590 MeV x 2600 μ A = 1.53 MW | 1.44 |
| • ~2010 (??) | 590 MeV x 3000 μ A = 1.77 MW | 1.67 |

➤ Reliability/availability: Accelerator ~90% SINQ 99%: No margin!

➤ Target development

SINQ target development

from visions to achievements

1990: Vision or Fiction?

**SINQ target concept
Proposal 1990:
Liquid Metal Target
on the basis of LBE
(lead-bismuth-eutectic)**

**From: G. Bauer et al., in
Proc. ICANS-XI (1990)
Internatl. Collaboration on
Advanced Neutron Sources**




Fig. 3 Vertical section (right) and cut away view (left) of the liquid Pb-Bi target for SINQ. All connections to the target are made via four connector plates at the target head.


SINQ target development

~~from visions to~~ achievements


The SINQ Target Mark 2: Solid target with Zircaloy rods

equipped with thermocouples and test specimen rods


as manufactured



after 2 years of service
(6800 mAh of 570 MeV protons)




Yearly Production Data of SINQ




SINQ-Target Mark 3:

⇒ **Solid target: Lead clad in steel tubes**



SINQ-Target Mark 4:

⇒ **Solid target: Lead clad in steel tubes, partly clad in Zircaloy**




ZrPb-
Canneloni

in service since
end of April 2004

Target development

**General goal:
highest neutron yield**



**SINQ-Target
Mark 3,
view from
beam entrance**

➤ **solid targets:**

- | | <u>rel. yield factor</u> |
|--|--------------------------|
| • Solid Zircaloy rods: first target | 1 (ref.) |
| • Steel-clad Lead: present target | —————→ 1.42 |
| • Zircaloy-clad Lead: in test phase | calc. 1.7 – 1.8 |
| • Steel-clad U-10Mo: option not pursued | calc. 2.0 – 2.1 |

➤ **liquid metal target:**


Lead-Bismuth-Eutectic (MEGAPIE experiment)	calc. 1.9 – 2.1
---	------------------------

SINQ target development

materials irradiation and test program


STIP *) :

SINQ Target Irradiation Program




SINQ-Target Mark 3

*) presentation by **Yong Dai**
Wednesday 10:30 a.m.




STIP-II PbBi Rod

Before irradiation



After irradiation (max dose: 20 dpa)




Target Rod B:

It contains a PbBi (about 38 g) filled T91 capsule. Inside PbBi there are about 50 test samples for studying irradiation assisted corrosion effects of PbBi on different kinds of materials.

Approaching a lifetime assessment for the MEGAPIE target window:

Extensive materials studies within **STIP**: the **SINQ Target Irradiation Program**


A martensitic steel
T91 (9Cr2WTaV)
tensile specimen
irradiated in liquid
Lead-Bismuth-Eutectic




After 12 dpa (2 years of irradiation) at 210 to 250°C:
NO severe LBE corrosion and embrittlement effects

STIP-II Hg Rod

Before irradiation



After irradiation (max dose: 20 dpa)



Target Rod A:

It contains three Hg (about 19 g in total) filled capsules and one steel sample package. There is about 25% free space in each Hg filled capsule.



LiSoR: Liquid Solid Reaction

LiSoR Test-section:
designed: Subatech, France

Investigation of T91 steel under


- Irradiation (72 MeV protons)
- flowing LBE
- mechanical stress

LiSoR samples (cross sections):
outside inside of beam spot





SINQ Target Safety Hull:

γ -mapping of the beam footprint



Tensile tests after one year of irradiation



SINQ target development

the future

MEGAPIE

A liquid metal target for SINQ

MEGAwatt Pilot Experiment:

- Joint international initiative to design, built, operate and explore a liquid metal spallation target on the basis of Lead-Bismuth-Eutectic (LBE) for 1 MW beam power


Goals of MEGAPIE:

- Increase the neutron flux at SINQ
- Demonstrate the feasibility of a liquid metal target for high-power ADS applications




MEGAPIE target features

target
head




Electro-
magnetic
pumps



Heat
exchanger



Safety
hull





Beam
window

Manufacturing the MEGAPIE target

Heat Exchanger



Flow guide Tube




Megapie target reception at PSI (July 2005)



For details on MEGAPIE see:
**Presentation from
Friedrich Groeschel, today, 2:30 p.m.**


Thermal neutron flux



Thermal ($E < 0.625$ eV) neutron flux maps (neutrons/cm²/s/mA)

Development of Research Neutron Sources

"Top of the line"



Target design – irradiation positions






Figure 10: Irradiation positions in SING-target tubes.

Mark III (current)

Megapie




Neutron flux peaks



proton flux

Mark III (current)


Megapie




Proton flux maps ($\text{protons}/\text{cm}^2/\text{s}/\text{mA}$)

total neutron flux

Mark III (current)



Megapie




Total neutron flux maps (neutrons/cm²/s/mA)

proton flux LBE target

Irradiation position:
high flux of fast neutrons

3×10^{14} fast neutrons/cm²/s

$< 5 \times 10^{13}$ thermal neutrons/cm²/s



Proton flux maps (protons/cm²/s/mA)

SUMMARY

➤ Proton accelerator:

- at present: **highest CW beam power** worldwide
- **upgrade program** from now 1MW to **1.6 MW** to be launched

➤ Target development:

- from **visions** (early LBE target concept)
- via **achievements**: solid target on the basis of Zircaloy and steel-
Zircaloy-clad Lead
- to **the future**: from LBE target (MEGAPIE) to a liquid metal
target with dedicated (fast neutrons) materials irradiation insert
- This would clearly be a **unique possibility** to test new materials for fission, fusion and spallation in realistic irradiation fields in SINQ

Acknowledgement

- **Hajo Heyck** and the operational team
- **Yong Dai** and the materials team
- **Friedrich Groeschel** and the
MEGAPIE team