

List of Figures

1	Organization chart for Study-II.	xiii
2	Schematic of the Neutrino Factory facility	xv
1.1	Muon decays in a straight section <i>vs.</i> muon energy	1 - 4
1.2	Mercury jet target geometry.	1 - 5
1.3	Mercury enclosure, mercury-pool beam dump	1 - 5
1.4	Transverse emittance along the cooling channel.	1 - 7
1.5	Top view and cross section through ring and berm	1 - 9
2.1	AGS proton driver layout.	2 - 3
2.2	AGS injection simulation. The abscissa is phase.	2 - 5
2.3	Configuration of the cavities within the cryo-modules (cryostats).	2 - 7
2.4	Current and voltage cycle for 2.5 Hz operation	2 - 11
2.5	Schematic of power supply connections to the AGS magnets	2 - 12
2.6	Bunch pattern for using harmonic 24 to create 6 bunches	2 - 14
3.1	Pion production data from BNL E910 and from MARS	3 - 2
3.2	Pion yield <i>vs.</i> atomic number	3 - 3
3.3	Pion yield in Hg <i>vs.</i> θ_p and R_{Hg}	3 - 4
3.4	Target, capture solenoids and mercury containment	3 - 6
3.5	Layout of the target area	3 - 7
3.6	Beam-induced breakup of a mercury jet, calculated	3 - 8
3.7	Beam-induced breakup of a mercury jet, experiment	3 - 9
3.8	Axial magnetic field profile	3 - 11
3.9	Disruption of a mercury jet by a magnetic field	3 - 12
3.10	Damping of a mercury jet by a magnetic field	3 - 13
3.11	Beam dump, shielding and mercury containment detail	3 - 14
3.12	The overall target support facility.	3 - 14
3.13	Transverse section of the target system at $z = 5.2$ m	3 - 15

3.14	Pion yield and ΔT <i>vs.</i> $r_{\text{target}}/r_{\text{beam}}$	3 - 15
3.15	Energy deposited in a mercury target <i>vs.</i> z	3 - 16
3.16	Radiation dose in the target system for $-2 < z < 6$ m	3 - 17
3.17	Particle fluxes in the magnet system <i>vs.</i> r	3 - 19
3.18	Power density and radiation dose in the target system <i>vs.</i> r	3 - 20
3.19	Power and radiation dose in the Be window at $z = 6.1$ m	3 - 21
3.20	Flux of neutrons with $E > 100$ keV in the target system	3 - 22
3.21	Radiation dose in the target system for $-2 < z < 36$ m	3 - 23
3.22	Longitudinal section through target module	3 - 24
3.23	Radial section through the target module	3 - 25
3.24	On-axis field of pion capture magnet near the target region	3 - 32
3.25	Cryostat and coils of the pion capture magnet	3 - 33
3.26	Mineral-insulated hollow conductor	3 - 35
3.27	End view and section of resistive insert magnet	3 - 36
3.28	Superconducting magnet of same scale as pion capture magnet	3 - 36
3.29	Concept of high-current cable-in-conduit conductor	3 - 37
3.30	The cable-in-conduit conductor for the ITER central solenoid	3 - 38
3.31	Cumulative axial force on components of the pion capture magnet	3 - 39
3.32	On-axis field of pion capture magnet for $3 < z < 18$ m	3 - 40
3.33	ANSYS modeling of the proton beam window	3 - 41
3.34	Three double window designs for the downstream beam window	3 - 43
3.35	Pressure profile in the Hg jet	3 - 44
3.36	The mercury pool/proton beam absorber	3 - 45
3.37	Mercury flow loop schematic layout.	3 - 46
3.38	Arrangement of the mercury flow loop components	3 - 48
3.39	The beryllium window in a replaceable solenoid	3 - 49
3.40	Side view of the target facility	3 - 50
3.41	Plan view of the target facility	3 - 50
3.42	Vacuum vessel upstream of the target region	3 - 51
3.43	Main cryostat containment for SC 1-5	3 - 52
3.44	Typical construction of the shield modules	3 - 53
3.45	View of the resistive insert magnets	3 - 54
3.46	Section cut and end view of the resistive coil module	3 - 56
3.47	Decay channel cryostat module	3 - 57
3.48	Installation sequence for the high field coils SC 1 and H-C 1-3	3 - 58
3.49	The target facility maintenance cell	3 - 59
3.50	Facility shield over the decay channel	3 - 61

4.1	Beam longitudinal profile without phase rotation.	4 - 2
4.2	Beam longitudinal profile with non-distorting phase rotation.	4 - 3
4.3	Location of $n\pi$ -resonances in a periodic solenoidal field.	4 - 4
4.4	Particle losses after a 50 m drift in a 3 T, 1 m periodic solenoidal field	4 - 5
4.5	Pulse shapes of the induction linacs	4 - 6
4.6	Cross section of two induction units.	4 - 7
4.7	Power deposition along the length of the first minicool section.	4 - 9
4.8	Transverse power deposition in the first minicool section.	4 - 11
5.1	Magnet configuration and axial field and beta function	5 - 3
5.2	Momentum-time distributions through the buncher.	5 - 5
5.3	Momentum-time distributions through the buncher (continued).	5 - 6
5.4	Correlations	5 - 8
5.5	The longitudinal component of the magnetic field	5 - 11
5.6	Beta function and phase advance in the (1,3) lattice	5 - 12
5.7	The $\beta_{\perp}$ function <i>vs.</i> momentum	5 - 14
5.8	The longitudinal field on axis for the entire SFOFO channel	5 - 19
5.9	Beta function in the buncher and cooling section	5 - 21
5.10	The averaged $\beta_{\perp}$ function <i>vs.</i> length	5 - 22
5.11	Transverse and longitudinal emittances in the cooling channel	5 - 23
5.12	The longitudinal and transverse emittances	5 - 24
5.13	Particle transmission: in the buncher and cooling sections	5 - 25
5.14	μ/p yield ratio for the two transverse emittance cuts	5 - 26
5.15	Transmission of the front end for different <i>rms</i> tilt angles.	5 - 30
5.16	Transmission of the front end for rms translation	5 - 31
5.17	A histogram of the performance of 35 SFOFO channels	5 - 32
5.18	μ/p <i>vs.</i> N_{μ} in a bunch, assuming a Gaussian self-field.	5 - 33
5.19	Schematic of convection design.	5 - 35
5.20	Schematic of ASME torispherical head on cylindrical vessel	5 - 35
5.21	Window design for the SFOFO lattice 1	5 - 37
5.22	Absorber assembly for SFOFO lattice 2	5 - 38
5.23	The scale of discontinuities in β function	5 - 39
5.24	Possible location for diagnostic instrumentation	5 - 43
5.25	Engineering rendering of the 1.65 m cooling lattice cell	5 - 45
5.26	Engineering rendering of the 2.75 m cooling lattice cell	5 - 46
5.27	Magnet cross section for the 2.75 m long cooling cell	5 - 47
5.28	Magnet cross-section for the 1.65 m cooling cell	5 - 47
5.29	Transverse emittance as a function of distance	5 - 49

5.30	Muons per incident proton as a function of distance	5 - 50
5.31	Kinetic energy distribution of initial pions	5 - 50
5.32	Beta function at the end of matching	5 - 53
5.33	Coil dimensions and axial field	5 - 54
5.34	Beta function <i>vs.</i> z	5 - 55
5.35	rm radius <i>vs.</i> z	5 - 55
5.36	Losses in the cooling to acceleration matching section	5 - 56
5.37	Emittances <i>vs.</i> z	5 - 57
6.1	Layout of the muon accelerator driver.	6 - 3
6.2	Decay of muons in acceleration.	6 - 3
6.3	Layouts of cryomodules.	6 - 5
6.4	Beam envelopes along the linear accelerator.	6 - 6
6.5	Beta functions along the linear accelerator.	6 - 6
6.6	Electrical circuit model for calculation of cavity coupling.	6 - 6
6.7	Dependence of cavity voltage on frequency.	6 - 7
6.8	Attenuation of electromagnetic waves between two cavities.	6 - 8
6.9	Layout of short solenoid and plot of its magnetic field lines.	6 - 9
6.10	Dependence of the magnetic field on longitudinal coordinate.	6 - 9
6.11	RF (left) and synchrotron (right) phases along the linac.	6 - 10
6.12	Beam boundary inside separatrix at the beginning of the linac.	6 - 11
6.13	Beam boundary at the beginning, middle, and end of the linac.	6 - 11
6.14	Dependence of the maximum beta function with the tune advance per cell.	6 - 12
6.15	Dependence of beta function maximum on momentum.	6 - 12
6.16	Relative emittance change.	6 - 13
6.17	Longitudinal phase space in the linac.	6 - 14
6.18	Beam intensity, momentum spread, emittance, and envelope along the linac.	6 - 14
6.19	Diagram of the injection chicane.	6 - 15
6.20	Beta functions and dispersion in the injection chicane.	6 - 15
6.21	Beam envelopes in the injection chicane.	6 - 16
6.22	Variation of beam emittance and beam envelopes along the linac.	6 - 16
6.23	Layout of the injection chicane at the separation point.	6 - 17
6.24	Cross section of the injection chicane at the separation point.	6 - 18
6.25	Cross section of the injection chicane at a focusing quadrupole.	6 - 18
6.26	Geometric layout of odd numbered arcs.	6 - 21
6.27	Boundaries of longitudinal phase space in the recirculator.	6 - 23
6.28	Boundaries of longitudinal phase space for first and last bunch.	6 - 24
6.29	Layout of an RLA linac period.	6 - 24

6.30	Beta functions for the first pass of the first RLA linac.	6 - 24
6.31	Beta functions for the last pass of the first RLA linac.	6 - 25
6.32	Beam envelopes for the first pass of the first RLA linac.	6 - 25
6.33	Beam envelopes for the last pass of the first RLA linac.	6 - 25
6.34	Beam envelopes for the first pass of the second RLA linac.	6 - 25
6.35	Beam envelopes for the last pass of the second RLA linac.	6 - 26
6.36	Tune diagram for one period of the first pass in the RLA linac.	6 - 27
6.37	RF phase for different passes through the RLA linacs.	6 - 29
6.38	Arc 1 optics.	6 - 29
6.39	Arc 2 optics.	6 - 30
6.40	Arc 3 optics.	6 - 30
6.41	Arc 5 optics.	6 - 30
6.42	Arc 7 optics.	6 - 31
7.1	Storage ring diagram.	7 - 2
7.2	Fraction of decays in a straight <i>vs.</i> L_S/L_A	7 - 2
7.3	Photograph of a pancake coil.	7 - 4
7.4	Demonstration of the effect of inter-magnet spacing on arc length.	7 - 5
7.5	Arc magnet layout.	7 - 6
7.6	Eigenplanes for the pure skew decoupled lattice	7 - 7
7.7	Generating upright quadrupole in bends.	7 - 7
7.8	Layout of the arc.	7 - 8
7.9	Beta functions for the storage ring.	7 - 9
7.10	Beta functions and the dispersion function for arc.	7 - 10
7.11	Diagram showing cancellation of sextupole nonlinearities.	7 - 11
7.12	Arc magnet cross section.	7 - 12
7.13	Cross-section as one approaches the end of the top coil.	7 - 12
7.14	Longitudinal variation in the sextupole field	7 - 13
7.15	Arc coil configuration used for tracking.	7 - 14
7.16	Tracking particles in the arc cell.	7 - 16
7.17	Low-amplitude tracking in the arc cell.	7 - 16
7.18	Tracking with end fields.	7 - 17
7.19	Tracking with additional multipole components.	7 - 18
7.20	Tracking with reduced multipole components.	7 - 19
7.21	Field profile of solenoidal field component from the bar magnet model.	7 - 20
7.22	Tracking with solenoidal fields added.	7 - 21
7.23	An engineering design of the magnet cross section.	7 - 22
7.24	Three-dimensional view of the storage ring magnets.	7 - 22

7.25	Relative event rate at the detector.	7 - 25
7.26	Flux at the detector and the uncertainty in that flux.	7 - 26
8.1	Thomson TH 1801 multi-beam klystron.	8 - 6
8.2	Cross section of cooling channel equipment gallery.	8 - 7
8.3	Cooling channel equipment gallery, plan view.	8 - 7
8.4	Compact modulator	8 - 9
8.5	Profile of cavities for buncher and Lattice 1 cooling section.	8 - 13
8.6	Section of one cavity.	8 - 14
8.7	MAFIA model with two foils.	8 - 14
8.8	URMEL 2D E-field.	8 - 15
8.9	URMEL 2D azimuthal H-field.	8 - 15
8.10	Profile of cavities for Lattice 2 cooling section.	8 - 16
8.11	Lattice 2 cooling cavity. URMEL 2D E-field.	8 - 17
8.12	URMEL 2D azimuthal H-field	8 - 17
8.13	Layout of beryllium test window (all dimensions in mm).	8 - 18
8.14	Actual temperature profile for rf heating	8 - 18
8.15	ANSYS calculated temperature profile for thin window	8 - 19
8.16	ANSYS model showing buckling displacement	8 - 19
8.17	ANSYS calculated displacement <i>vs.</i> power	8 - 20
8.18	Stepped window concept.	8 - 20
8.19	Temperature profile of uniform thin window	8 - 20
8.20	Cooling channel Lattice 1, four cavities per cell.	8 - 22
8.21	Cooling channel Lattice 2, two cavities per cell.	8 - 22
8.22	402.5 MHz buncher harmonic cavity.	8 - 23
8.23	Q_0 <i>vs.</i> gradient for Nb/Cu CERN 400 MHz, LHC cavity.	8 - 27
8.24	Q_0 <i>vs.</i> gradient expected for 201.25 MHz cavity	8 - 28
8.25	Two-cell geometry: (left) small aperture; (right) large aperture.	8 - 29
8.26	Lorentz force detuning for 8 mm wall thickness cavity.	8 - 30
8.27	KEKB 508-MHz coupler.	8 - 34
8.28	TESLA-type HOM coupler.	8 - 35
8.29	Lowest vibrational mode of 2-cell cavity.	8 - 36
8.30	Long cryomodule.	8 - 37
8.31	LEP cryomodule.	8 - 37
9.1	Acceleration waveforms	9 - 2
9.2	Losses of amorphous alloys	9 - 4
9.3	Hysteresis for 2605SC and 2605S3A	9 - 5

9.4	Induction cell cross-sections	9 - 7
9.5	Pulse voltage breakdown	9 - 8
9.6	Flashover voltage	9 - 9
9.7	Current density	9 - 10
9.8	Magnetic materials losses	9 - 11
9.9	Hysteresis curves	9 - 12
9.10	Magnetic pulse compression	9 - 14
9.11	IL1 7-cell pulse generator	9 - 16
9.12	Pulse compression modulator	9 - 17
9.13	Metglas assembly	9 - 20
9.14	Seven cell housing	9 - 21
9.15	Six strut module	9 - 22
10.1	Induction cell and mini-cooling solenoid	10 - 2
10.2	Cross section of the induction linac superconducting coil	10 - 4
10.3	Induction cell solenoid cold mass support system and leads.	10 - 6
10.4	A cross section of the solenoids in the pion decay channel.	10 - 7
10.5	Cryogenic cooling system for a typical induction cell.	10 - 10
10.6	Cross section of the 1.65 m cell focusing magnets	10 - 12
10.7	Cryogenic cooling system for a cooling (“A”) coil	10 - 19
10.8	A cross section, parallel to the magnetic axis, of a short 1-m solenoid. . .	10 - 24
10.9	A cross section of the long 1.5 m solenoid	10 - 25
11.1	Magnet helium cooling circuit for the (“B”) coils	11 - 3
11.2	Magnet helium cooling circuit for the (“A”) coil in a 2.75 m cell	11 - 4
11.3	Helium cooling circuit for the (“A”) coils in a 1.65 m cell	11 - 5
11.4	Site layout.	11 - 7
13.1	Neutrino-induced dose around the arcs	13 - 8
13.2	Schematic representation of the neutrino radiation in the MuSR.	13 - 11
14.1	Grid of thin-walled tubes.	14 - 9
14.2	Continuous array of tubes.	14 - 10
14.3	Cavity impedance versus length for an ideal pillbox, $\beta = 0.87$	14 - 12
14.4	Schematic of multi-beam klystron	14 - 13
14.5	Cathode of Thompson multi-beam klystron.	14 - 14
14.6	Cavity of multi-beam klystron.	14 - 14
14.7	Klystron efficiency <i>vs.</i> beam perveance.	14 - 15
14.8	1 MW cw HOM-IOT.	14 - 15

14.9 Vertical dewar test.	14 - 17
14.10 Test pit (2.5 m diameter and 5 m deep) for 200 MHz cavities	14 - 17
14.11 Comparison of pipe-with bath-cooling for a 200 MHz cell	14 - 18
15.1 Measuring the ratio of $P(\bar{\nu}_e \rightarrow \bar{\nu}_\mu)$ to $P(\nu_e \rightarrow \nu_\mu)$	15 - 4
15.2 Fraction of neutrino events that produce a background signal	15 - 6
15.3 Reconstructed neutrino energy distribution	15 - 7
15.4 Distributions of the square of the muon momentum	15 - 8
15.5 A possible 50 kton Steel/Scintillator/PDT detector at WIPP	15 - 10
15.6 Block schematic of the UNO detector	15 - 12
15.7 Concept of multi-water tank Cerenkov counter	15 - 13
15.8 The WIPP area	15 - 14
A.1 Efficiency <i>vs.</i> capture field.	A - 6
A.2 Efficiency of three types of inserts in 20 T magnet	A - 7
A.3 Relative cost of pion capture magnet	A - 9
A.4 Final energy <i>vs.</i> time: baseline	A - 11
A.5 Final energy <i>vs.</i> time: IL1 and IL2 removed	A - 12
A.6 Efficiency <i>vs.</i> length of induction linacs	A - 13
A.7 Efficiency <i>vs.</i> length of cooling.	A - 14
B.1 Efficiency <i>vs.</i> proton bunch length.	B - 4
B.2 A conceptual illustration of the rotating band setup	B - 6
B.3 Passage of the proton beam through the target band	B - 7
B.4 A conceptual illustration of the cooling setup	B - 9
B.5 Predicted von Mises stress distribution	B - 11
B.6 Predicted time dependence of von Mises stresses	B - 12
B.7 Illustration of the particle motion (end view)	B - 16
B.8 Sketch of magnetic field on axis	B - 17
B.9 Sketch of the accelerator system	B - 18
B.10 Distribution of particles in longitudinal phase space	B - 19
B.11 Engineering drawing of a cooling channel unit cell	B - 21
B.12 Side view of a cooling cell	B - 24
B.13 Magnetic field <i>vs.</i> z	B - 25
B.14 The first matching section.	B - 26
B.15 The second matching section.	B - 27
B.16 The magnetic field on axis in the first-flip	B - 28
B.17 The magnetic field on axis at the second field-flip	B - 29

B.18 Step windows	B - 30
B.19 Nominal energy <i>vs.</i> z	B - 31
B.20 The absorber vessel	B - 32
B.21 Performance of the Double-Flip with a Gaussian beam	B - 33
B.22 Performance of the Double-Flip with a “realistic” beam	B - 33
B.23 Evolution of the longitudinal phase space	B - 34
B.24 Evolution of the beam size	B - 35
B.25 Evolution of p_y versus x	B - 36
B.26 Muon/proton yield at the end of the channel	B - 38
B.27 Performance <i>vs.</i> accelerator acceptance	B - 41
B.28 Schematic of conventional racetrack RLA.	B - 42
B.29 Schematic of dogbone RLA.	B - 42
B.30 Relative costs of RLA’s <i>vs.</i> number of passes.	B - 43
B.31 The Soudan Site	B - 45
B.32 Two views of the MINOS detector	B - 47