

List of Tables

1	Length of the main components of a Neutrino Factory.	xvi
2	Muon beam parameters along the length of the facility.	xvii
2.1	AGS proton driver parameters.	2 - 2
2.2	Comparison of H minus injection parameters	2 - 4
2.3	AGS injection parameters.	2 - 6
2.4	Parameters of the superconducting linacs.	2 - 8
3.1	Proton beam and mercury jet geometric parameters	3 - 5
3.2	Solenoid coil geometric parameters	3 - 10
3.3	Relevant properties of the mercury jet	3 - 11
3.4	Radiation doses and lifetimes of some components	3 - 18
3.5	Energy deposition by cell	3 - 18
3.6	Neutron flux in various cells	3 - 26
3.7	Activation in Curies for selected cells	3 - 27
3.8	Activation for cell 92 (mercury) 30 days after shutdown	3 - 28
3.9	Activation for cell 8 (tungsten-light water) 30 days after shutdown	3 - 29
3.10	Gamma ray source (gamma/s) in selected cells	3 - 30
3.11	Integrated neutron and gamma ray flux	3 - 30
3.12	Neutron energy spectrum for cell 207	3 - 31
3.13	Parameters of the hollow-conductor magnets	3 - 31
3.14	Parameters of the upstream SC solenoids	3 - 34
3.15	Maintenance requirements for the target system components	3 - 49
3.16	Solenoid coil sizes and weights, and shield module weights	3 - 55
3.17	Maintenance requirements for the target/capture components	3 - 62
4.1	Decay, phase rotation, and minicool solenoids	4 - 13
4.2	Power dissipation: positive muons	4 - 14
4.3	Power dissipation: negative muons	4 - 14

4.4	Absorber parameters	4 - 14
5.1	Matching section magnets.	5 - 2
5.2	RF buncher component locations	5 - 13
5.3	Length of the sections and integrated length	5 - 15
5.4	Geometry and current densities for the solenoids	5 - 16
5.5	Geometry and current density in the first matching	5 - 17
5.6	Geometry and j (A/mm^2) in the matching (1,3) and (2,1)	5 - 18
5.7	Geometry and rf parameters for the linac	5 - 20
5.8	Beam characteristics summary.	5 - 26
5.9	Coils parameters of the matching cells	5 - 52
6.1	Main parameters of the muon accelerator driver.	6 - 2
6.2	Main parameters of linear accelerator.	6 - 4
6.3	Parameters for the linear accelerator cryomodules.	6 - 5
6.4	Parameters of the injection chicane quadrupoles.	6 - 17
6.5	Parameters of injection dipoles.	6 - 19
6.6	Parameters for acceleration in the recirculator.	6 - 22
6.7	Parameters of the RLA linac periods.	6 - 26
6.8	Acceptable nonlinear fields of quadrupoles.	6 - 28
7.1	Muon storage ring parameters.	7 - 3
7.2	Input beam parameters.	7 - 5
7.3	Magnet parameters	7 - 9
7.4	Optical description and parameters for the arc cell	7 - 15
7.5	Multipole components in the arc cell	7 - 17
7.6	Linear tunes in each study case for the two orthogonal planes.	7 - 20
7.7	Field errors in the dipole magnet section.	7 - 23
7.8	Field errors in the skew quadrupole magnet section.	7 - 24
7.9	Required precision for muon beam measurements.	7 - 27
8.1	Parameters for the ideal and realistic NCRF cavities	8 - 3
8.2	Voltage and power requirements for the NCRF cavities	8 - 4
8.3	High-voltage modulator parameters.	8 - 10
8.4	NCRF systems AC power requirements.	8 - 10
8.5	Beryllium foil thicknesses	8 - 12
8.6	2-cell, 300 mm-diameter cavity parameters.	8 - 31
8.7	2-cell, 460 mm-aperture cavity parameters.	8 - 32
8.8	Short cryomodule parameters.	8 - 38

8.9	Intermediate cryomodule parameters.	8 - 38
8.10	Long cryomodule parameters.	8 - 39
8.11	SCRF overall parameters for a Neutrino Factory.	8 - 39
9.1	Induction accelerator parameters	9 - 13
9.2	Energy and power requirements	9 - 19
10.1	Sources of heat in a 1 m long induction cell magnet	10 - 9
10.2	Basic parameters for bunching and cooling cell	10 - 13
10.3	Solenoid parameters for the 2.75 m bunching and cooling cell	10 - 14
10.4	Solenoid parameters for the 1.65-m-long cooling cell.	10 - 15
10.5	Coil average j and I for bunching and cooling channels	10 - 17
10.6	Sources of heat	10 - 27
10.7	Stray field at various distances from the axis of a long cooling cell.	10 - 28
10.8	Superconducting solenoid parameters for the linear accelerator.	10 - 29
10.9	The sources of heat at 4.4 K and 40 K in a 1.5 m long focusing solenoid.	10 - 30
11.1	Devices and heat loads.	11 - 11
11.2	Load summary.	11 - 13
11.3	Load concentrations and percentages.	11 - 14
11.4	Load concentrations grouped by area, with 30% contingency.	11 - 15
14.1	Comparison of possible minicooling absorber materials.	14 - 6
14.2	Comparison between HOM-IOT and klystron	14 - 12
15.1	Event rates WIPP.	15 - 2
A.1	Construction Cost Rollup for Study-II	A - 4
A.2	Construction Cost Totals for Study-II	A - 5
A.3	Efficiency for three cooling lengths.	A - 14
B.1	Compressor ring parameters.	B - 2
B.2	rf parameters of compressor ring.	B - 2
B.3	Longitudinal parameters of compressor ring.	B - 3
B.4	Transverse parameters.	B - 3
B.5	Efficiency <i>vs.</i> proton bunch length.	B - 5
B.6	Specifications of the Inconel target band	B - 8
B.7	Parameters of the “realistic” beam	B - 20
B.8	Lists of parameters associated with the four sections	B - 22
B.9	Parameters associated with the two flip regions	B - 23

B.10 Parameters of the beam at the end of the cooling channel	B - 31
B.11 Performance dependency on rf cavity apertures.	B - 40
B.12 Event rates at possible detectors at Soudan and WIPP.	B - 44